

## WHEEL AND TYRE

E9DMAAB

On the wide fender equipped vehicles, aluminum wheels are standard equipment.  
The offset amount of wheel, reduced for the wider

fender installation, have contributed to wider track and better cornering performance.

### SPECIFICATIONS

<Vehicles for Europe>

Items	Vehicles with wide fender	Vehicles without wide fender
<b>Wheel</b> <b>Type</b> <b>Size</b> <b>Offset</b> mm (in.) Pitch circle diameter mm (in.) <b>Tyre</b> <b>Size</b>	Aluminum type 15 x 7JJ 10 (0.39) 139.7 (5.5)  265/70R15 110S	Steel type Aluminum type* <sup>1</sup> 15 x 6JJ 33 (1.29) 139.7 (5.5)  235/75R15 105S 215R15 100S* <sup>1</sup>
Tyre inflation pressure kPa (kg/cm <sup>2</sup> , psi) When 4 passengers Front Rear  When 4 passengers to max. load or trailer towing Front Rear	 180 (1.8, 26) 200 (2.0, 28)  180 (1.8, 26) 200 (2.0, 28)	 180 (1.8, 26) 200 (2.0, 28) 210 (2.1, 30)* <sup>2</sup>  180 (1.8, 26) 220 (2.2, 31) 230 (2.3, 33)* <sup>2</sup>

#### NOTE

\*<sup>1</sup>: Optional equipment

\*<sup>2</sup>: Tire inflation pressure for optional tyres