

WHEEL AND TYRE

E9DMAAB

On the wide fender equipped vehicles, aluminum wheels are standard equipment.
The offset amount of wheel, reduced for the wider

fender installation, have contributed to wider track and better cornering performance.

SPECIFICATIONS

<Vehicles for Europe>

Items	Vehicles with wide fender	Vehicles without wide fender
Wheel		
Type	Aluminum type	Steel type Aluminum type* ¹
Size	15 x 7JJ	15 x 6JJ
Offset	mm (in.) 10 (0.39)	33 (1.29)
Pitch circle diameter	mm (in.) 139.7 (5.5)	139.7 (5.5)
Tyre		
Size	265/70R15 110S	235/75R15 105S 215R15 100S* ¹
Tyre inflation pressure	kPa (kg/cm ² , psi)	
When 4 passengers		
Front	180 (1.8, 26)	180 (1.8, 26)
Rear	200 (2.0, 28)	200 (2.0, 28) 210 (2.1, 30)* ²
When 4 passengers to max. load or trailer towing		
Front	180 (1.8, 26)	180 (1.8, 26)
Rear	200 (2.0, 28)	220 (2.2, 31) 230 (2.3, 33)* ²

NOTE

*¹: Optional equipment

*²: Tire inflation pressure for optional tyres

<Vehicles for General Export>

Items	Canvas top and van		Wagon			
	GCC	Except for GCC	GCC		Except for GCC	
			With wide fender	Without wide fender	With wide fender	Without wide fender
Wheel						
Type	Steel type	Steel type	Aluminum type	Steel type	Aluminum type	Steel type
Size	16 x 5.50F 16 x 6JJ* ¹	16 x 5.50F 16 x 6JJ* ¹	15 x 7JJ	16 x 6JJ 16 x 5.50F* ¹	15 x 7JJ	16 x 6JJ 16 x 5.50F* ¹
Offset mm (in.)	33 (1.29)	33 (1.29)	10 (0.39)	33 (1.29)	10 (0.39)	33 (1.29)
Pitch circle diameter mm (in.)	139.7 (5.5)	139.7 (5.5)	139.7 (5.5)	139.7 (5.5)	139.7 (5.5)	139.7 (5.5)
Tyre						
Size	205/80R16 RF 104S 7.50-16 -6PRLT* ¹	205R16 RF 104Q 7.50-16 -6PRLT* ¹	31 x 10.50R15 6PRLT	205/80R16 RF 104S 7.50-16 -6PRLT* ¹	31 x 10.50R15 6PRLT	205R16 RF 104Q 7.50-16 -6PRLT* ¹
Tyre inflation pressure kPa (kg/cm ² , psi)						
Front	210 (2.1, 30) 200 (2.0, 29)* ²	210 (2.1, 30) 200 (2.0, 29)* ²	200 (2.0, 29)	210 (2.1, 30) 200 (2.0, 29)* ²	200 (2.0, 29)	210 (2.1, 30) 200 (2.0, 29)* ²
Rear	260 (2.6, 38) 240 (2.4, 35)* ²	260 (2.6, 38) 240 (2.4, 35)* ²	200 (2.0, 29)	260 (2.6, 38) 240 (2.4, 35)* ²	200 (2.0, 29)	260 (2.6, 38) 240 (2.4, 35)* ²

NOTE

*¹: Optional equipment*²: Tyre inflation pressure for optional tyres

<Vehicles for Australia>

Items	Vehicles with wide fender	Vehicles without wide fender	
		With leaf spring rear suspension	With 3-link, coil spring rear suspension
Wheel			
Type	Aluminum type	Steel type	Steel type
Size	15 x 7JJ	16 x 5.50F 16 x 6JJ*	15 x 6JJ
Offset mm (in.)	10 (0.39)	33 (1.29)	33 (1.29)
Pitch circle diameter mm (in.)	139.7 (5.5)	139.7 (5.5)	139.7 (5.5)
Tyre			
Size	265/70R15 110S	205R16 RF 104Q	P235/75R15
Tyre inflation pressure kPa (kg/cm ² , psi)			
When not loaded			
Front	180 (1.8, 26)	210 (2.1, 29)	180 (1.8, 26)
Rear	200 (2.0, 28)	240 (2.4, 35)	200 (2.0, 28)
When loaded			
Front	180 (1.8, 26)	230 (2.3, 33)	180 (1.8, 26)
Rear	200 (2.0, 28)	260 (2.6, 38)	240 (2.4, 35)

NOTE

*: Optional equipment