

SPECIFICATIONS

COIL SPRINGS

Spring Number	X5K Steel	Bar Dia. mm	Free Height mm		Number Of Coils	Coil weight Kg	Spring Rate	
			A	B			lbf / in	N / mm
OME500	X	14.5	385	385	5.4	3.5	155	27
OME501		15	350	350	7.3	4.5	175	30.6
OME502	X	16	350	350	6.0	4.6	245	42.9
OME503		15	342	342	7.0	4.1	185	42.9
OME504	X	14.5	355	355	5.4	3.4	155	27
OME505		15	330	330	7.3	4.2	175	30.6
OME506		15	330	330	5.1	3.5	180	31.5
OME507		15	338	338	5.1	3.5	180	31.5
OME508		15	315	315	5.6	3.7	180	31.5
OME601		18	350	350	8.3	5.5	650	113.8
OME602	X	16	392	392	8.2	5.9	180	31.5
OME603	X	17	410	410	7.0	6.6	188	32.9
OME604	X	17	400	400	6.0	5.7	227	39.8
OME605	X	18	315	315	7.8	5.0	730	127.8
OME606	X	18	320	320	7.8	5.0	730	127.8
OME607	X	17	370	370	10.5	5.8	480	84
OME608	X	17	380	380	10.5	5.8	480	84
OME609	X	19	440	440	8.0	7.8	390	68
OME610	X	20	430	430	8.0	8.7	460	80
OME611		18	310	310	7.8	5.0	730	127.08
OME612	X	20	415	415	11.0	9.1	740	129.6
OME613	X	20	435	435	11.0	9.1	740	129.6
OME614	X	20	425	425	11.0	8.9	740	129.6
OME615	X	13	510	510	10.0	3.8	120	21
OME616	X	14	490	490	10.5	4.6	135	23.6
OME617	X	15	430	430	7.0	4.1	160	28
OME618	X	16	435	445	7.75	5.3	175	30.7
OME619	X	14	515	515	10.5	4.6	135	24.6
OME620	X	15	450	450	9.0	4.5	200	35
OME621	X	14	520	520	9.5	4.8	150	26.3
OME622	X	14.5	375	375	7.0	3.5	200	35
OME700	X	18	420	420	8.75	5.8	625	109
OME701	X	19	425	425	9.5	7.0	720	126
OME702	X	18.5	430	430	9.5	6.6	625	109
OME703	X	19	435	435	9.5	7.0	720	126
OME720	X	19	420	410	8.9	9.9	270 / 350	47 / 61
OME721	X	19	440	430	8.9	9.9	270 / 350	47 / 61
OME722	X	19	440	430	7.2	8.0	275	48
OME723	X	20	450	440	7.2	8.9	340	59.5
OME724	X	21	445	435	7.2	9.9	400	70
OME725	X	22	445	435	7.7	11.7	440	77
OME743	X	21	360	360	8.6	8.8	830	145
OME744		18	400	400	9.7	6.7	430	93
OME745		19	390	390	9.7	7.2	670	117
OME746	X	20	370	370	8.6	8.1	680	119
OME751	X	15	390	380	6.6	3.9	230	40
OME752	X	17	440	440	9.0	6.7	270	47
OME754	X	20	435	435	6.9	8.4	420	73.5
OME755	X	18	435	435	6.8	6.6	300	52.5
OME760		15	395	385	9.0	6.8	180 - 250	35 - 44
OME761	X	15	400	390	7.5	4.4	200	35
OME762	X	17.5	420	410	8.6	7.0	300 - 340	52 - 60
OME763	X	18	420	410	7.8	6.8	360	63
OME764	X	16	430	420	8.0	5.4	220	38.5
OME766	X	16	420	420	7.5	5.1	250	44

cont.