

# SPECIFICATIONS

## COIL SPRINGS

Spring Number	X5K Steel	Bar Dia. mm	Free Height mm		Number Of Coils	Coil weight Kg	Spring Rate	
			A	B			lbf / in	N / mm
OME901	X	16	395	385	6.3	4.6	220	38.5
OME902		18	340	340	8.4	5.5	650	113.8
OME903	X	16	380	380	7.3	5.3	210	36.8
OME904		15	410	410	6.8	4.4	170	29.8
OME905	X	17	313	313	6.0	4.7	360	63
OME907	X	17	370	370	5.3	5.2	213	37.3
OME908	X	16	295	295	7.3	4.5	368	64.4
OME910	X	17	400	390	7.5	7.0	150 - 260	26 - 45.5
OME911	X	16	400	390	7.5	7.0	140 - 230	24.5 - 40
OME912		15	420	420	10.8	5.6	180 - 300	31.5 - 52.5
OME913		15	390	390	9.3	4.8	180 - 300	31.5 - 52.5
OME914		18	330	330	8.2	5.0	650	114
OME915		18	345	345	8.2	5.5	650	113.8
OME917	X	21	345	335	7.3	8.6	700 - 900	122 - 157
OME918	X	22	338	328	7.3	9.5	860 - 1000	150 - 175
OME919		15	430	430	10.8	5.7	200 - 280	35 - 49
OME920		14	430	430	8.0	3.6	190	33
OME921	X	16	385	385	6.8	5.3	200	35
OME922	X	14	360	360	6.1	3.3	140	24
OME923	X	16	395	395	6.8	5.3	200	35
OME924		19	340	340	8.2	6.2	790	138
OME925	X	16	385	385	10.8	5.4	375	65.7
OME926	X	16	392	392	10.8	5.4	375	65.7
OME927	X	16	394	394	10.3	5.2	400	70
OME928	X	16	410	410	6.8	5.0	200	35
OME929	X	16	420	420	10.8	6.6	240 - 300	42 - 52.5
OME930	X	14	475	465	9.8	3.9	160	28
OME931		14	510	500	11.9	5.1	140	24.5
OME932	X	14	480	470	11.2	4.8	140	24.5
OME933	X	14	495	485	11.2	4.8	140	24.5
OME934	X	14	510	500	10.0	4.0	160	28
OME935	X	14	420	410	9.8	4.1	180	31.5
OME936		15	420	410	10.0	4.9	220	38.5
OME937		15	400	400	7.3	4.3	220	38.5
OME938		18	400	390	7.5	7.7	205 - 290	36 - 51
OME940		14	380	370	8.6	3.8	190	33
OME941		15	390	375	7.2	4.4	140	24.5
OME942	X	15.5	380	365	6.6	5.2	160	28
OME943		15	370	360	8.6	4.4	230	40.3
OME944	X	15	395	385	8.0	4.5	190	33
OME945	X	16	350	340	7.5	4.7	240	42
OME947	X	16	340	340	5.8	4.5	170	29.8
OME948	X	16	340	340	5.6	4.3	200	35
OME949	X	17	370	355	7.1	5.7	216	37.8
OME950	X	16	300	300	8.5	4.1	540	95
OME951		15	290	290	8.5	3.6	440	77
OME952	X	12	345	345	11.0	2.5	140	24.5
OME953	X	16	285	285	8.5	4.3	540	94.5
OME954	X	12	340	340	8.5	2.2	180	31.5
OME955		13	350	350	10.0	3.1	200	35
OME956	X	16	330	330	8.5	2.8	500	88
OME959	X	16	310	310	8.5	4.1	540	94.5
OME960		15	300	300	8.5	3.7	440	77
OME961		13	340	340	10.0	3.0	200	35
OME962	X	16	320	320	8.5	4.1	540	95

cont.